



EPDM GENERAL PURPOSE



- Application** : Air, water, agricultural spray solutions, and other dilute chemicals Excellent resistance to heat and weathering Also resists animal fats, vegetable oils.
- Cover** : Smooth red abrasion and weather resistant EPDM synthetic rubber
- Reinforcement** : Multiple layers of synthetic yarn
- Tube** : Synthetic oil mist resistant EPDM synthetic rubber
- Temperature** : -30C to +93C(-20F to +200F)

Nom. I.D	Nom. O.D	PSI	Weight (lbs)	Std Pack Qty	Part #
1/4"	0.55"	250	0.13	300'	GPE-025-250
5/16"	0.63"	250	0.16	300'	GPE-031-250
3/8"	0.68"	150	0.15	300'	GPE-038-150
3/8"	0.67"	200	0.16	300'	GPE-038-200
3/8"	0.71"	250	0.19	300'	GPE-038-250
1/2"	0.83"	200	0.23	300'	GPE-050-200
1/2"	0.87"	250	0.27	300'	GPE-050-250
5/8"	0.98"	250	0.31	300'	GPE-063-250
3/4"	1.16"	250	0.42	300'	GPE-075-250
1"	1.42"	200	0.55	300'	GPE-100-200
1-1/4"	1.77"	150	0.62	100'	GPE-125-150
1-1/2"	2.00"	150	0.73	100'	GPE-150-150
2"	2.50"	150	1.10	100'	GPE-200-150

Cut Lengths : Plus 5%

Standard Lengths : 1/4"- 1" 50'/100'/300' reels approx, 1-1/4" - 1-1/2" 50'/100'/400'/500' reels approx, 2" 50'/100'/300' reels approx

Recommended Couplings : High Pressure 1" - 1-1/2" for air service if the working pressure exceeds 150 psi. High Pressure, Short shank, universal, or Combination nipples all other sizes.