



FLANGED END



WELD/THREAD END



SWEAT END

CONNECTALL

COMPENSATORS

SMALL DIAMETER

ConnectAll Compensators are perfect for pipe diameters up to 4" when axial movement is required due to thermal expansion. They are stocked with both 2" and 3" compression ability in flanged, weld, thread, and sweat ends.

For greater movements and larger diameters, check our Model EP expansion joints.

Maximum Working Pressure1	75 psi
Working Temperature	750 F
Test Pressure2	50 psi
Bellows	4 S/S

SIZE	COMPRESSION	END CONFIGURATION					
		FLANGED		WELD/THREAD END		SWEAT ENDS	
		OAL (in)	WT (lbs)	OAL (in)	WT (lbs)	OAL (in)	WT (lbs)
3/4"	2" 3"	12-3/4 16-1/2	8 9	12-3/4 16-1/2	3	11 14-7/8	3/4 1
1"	2" 3"	13-1/4 16-1/2	9 10	13-1/4 16-1/2	4 4	11-1/4 15-1/8	1 1-1/2
1-1/4"	2" 3"	13-1/4 16-1/2	12 13	13-1/4 16-1/2	5 5	12-1/2 16-3/8	1-1/2 2
1-1/2"	2" 3"	14-5/8 17-1/2	14 15	14-5/8 17-1/2	7 6	12-7/8 16-3/4	2 3
2"	2" 3"	14-5/8 17-1/2	18 20	14-5/8 17-1/2	10 8	13 17	3 4
2-1/2"	2" 3"	16 18-3/4	29 29	16 18-3/4	14 14	13-1/4 17	4 5
3"	2" 3"	16 19-1/4	34 36	16 19-1/4	18 16	14 18	4-1/2 6
4"	2" 3"	16-3/8 19-1/4	47 44	16-3/8 19-1/4	25 22	-	-