

MARINE EXHAUST HARDWALL



- Application** : Marine exhaust applications, and other general applications where non-standard sizes are specified. Meets SAEJ 2006 R1
- Cover** : Black heat and weather resistant synthetic rubber with blue identification stripe.
- Reinforcement** : High tensile wire helix embedded between layers of textile cords.
- Tube** : Black heat resistant rubber specially compounded for wet marine exhaust service.
- Temperature** : -40C to +100C(-40F to +212F)

Nom. I.D	Nom. O.D	Weight (lbs)	Std Pack Qty	Part #
7/8"	1.25"	0.50	100'	MXH-088
1"	1.38"	0.57	100'	MXH-100
1-1/8"	1.40"	0.58	100'	MXH-113
1-1/4"	1.69"	0.68	100'	MXH-125
1-5/16"	1.60"	0.73	100'	MXH-131
1-3/8"	1.81"	0.75	100'	MXH-138
1-1/2"	1.81"	0.82	100'	MXH-150
1-5/8"	1.97"	1.10	100'	MXH-163
1-3/4"	2.09"	1.06	100'	MXH-175
1-7/8"	2.20"	1.14	100'	MXH-188
2"	2.32"	1.33	100'	MXH-200
2-1/8"	2.50"	1.39	100'	MXH-213
2-1/4"	2.60"	1.54	100'	MXH-225
2-3/8"	2.68"	1.71	100'	MXH-238
2-1/2"	2.81"	1.82	100'	MXH-250
2-5/8"	3.00"	2.06	100'	MXH-263
2-7/8"	3.35"	2.08	100'	MXH-288
3"	3.54"	2.12	100'	MXH-300
3-1/8"	3.70"	2.35	100'	MXH-313
3-1/2"	4.09"	2.62	100'	MXH-350
4"	4.57"	3.02	100'	MXH-400
4-1/8"	4.64"	2.75	100'	MXH-413
4-1/2"	5.12"	3.57	100'	MXH-450
5"	5.55"	3.59	100'	MXH-500

Cut Lengths : Plus 10%

Standard Lengths : 100'

Recommended Couplings : Cam and groove, combination nipples