




SATURN GREEN PVC WATER S&D



- Application** : An economical, flexible hose for construction pumps, septic tank & marine pump-out service. Resistant to some chemicals, mild acids & alkalis. Consult us for recommendations.
- Cover** : Clear abrasion and weather resistant PVC.
- Reinforcement** : Green PVC helix.
- Tube** : Smooth clear PVC.
- Temperature** : -20C to +65C(-5F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4	0.95	29	2.00	90	0.160	100	SATG-075
1	1.24	29	3.00	85	0.260	100	SATG-100
1 1/4	1.54	29	4.00	80	0.340	100	SATG-125
1 1/2	1.81	29	6.00	70	0.440	100	SATG-150
2	2.29	29	5.00	65	0.570	100	SATG-200
2 1/2	2.85	29	6.00	60	0.870	100	SATG-250
3	3.43	29	12.00	60	1.210	100	SATG-300
4	4.45	29	10.00	50	1.780	100	SATG-400
6	6.67	28	25.00	35	3.700	100	SATG-600
8	8.82	28	30.00	25	6.070	20	SATG-800

Cut Lengths : Plus 10%

Standard Lengths : 100'

Safety Information : Suction and Pressure ratings are based on a temperature of 20C (68F), reduce by 50% at maximum working temperature

Recommended Couplings : Cam and groove or short shank