




SATURN PVC WATER S&D



- Application** : An economical, flexible hose for construction pumps, septic tank & marine pump-out service. Resistant to some chemicals, mild acids & alkalis. Consult us for recommendations. Specially formulated compounds and a slightly corrugated cover allow for increased flexibility at low temperatures.
- Cover** : Clear abrasion and weather resistant extra soft PVC.
- Reinforcement** : Blue PVC helix.
- Tube** : Smooth clear extra soft PVC.
- Temperature** : -40C to +65C(-40F to +150F)

Nom. I.D (in)	Nom. O.D(in)	Vacuum ("Hg)	Bend Radius (in)	PSI	Weight (lbs)	Std Pack Qty	Part #
3/4	0.93	29	1.50	45	0.120	100	SAT-075
1	1.22	29	2.00	40	0.180	100	SAT-100
1-1/4	1.48	29	2.50	35	0.180	100	SAT-125
1-1/2	1.83	29	2.50	35	0.330	100	SAT-150
2	2.35	29	3.00	35	0.440	100	SAT-200
2-1/2	2.90	29	5.00	30	0.600	100	SAT-250
3	3.50	29	6.00	30	0.850	100	SAT-300
4	4.63	29	9.00	25	1.340	100	SAT-400
6	6.73	28	11.00	25	2.720	100	SAT-600

Cut Lengths : Plus 10%

Standard Lengths : 100'

Safety Information : Suction and Pressure ratings are based on a temperature of 20C (68F), reduce by 50% at maximum working temperature

Recommended Couplings : Cam and groove or short shank