



*ASI HYDRAULICS POWER UNITS*  
**DIESEL ENGINE DRIVEN**

## Standard Features:

- Dependable diesel engines.
- The flattop frame is specifically designed with forklift pockets for easy handling.
- Pendant controls motor speed, hydraulic flow and direction.
- Minimal hydraulic oil temperature rise developed from power unit.
- NEMA 4 electrical controls.
- Powder-coated for durability.

## Typical Applications:

- Outdoor Applications
- Mining Applications
- Portable Line Boring
- Portable Machining
- Conveyors
- Service Trucks
- Railroad
- Shovel & Drag Line Repair
- Portable Boring
- Large Pipe Prep

## Specifications

<b>Frame:</b>	Powder coated finish
<b>Motor:</b>	26 HP
<b>Oil Capacity:</b>	Approx. 20 gallons AW32 or AW36
<b>Pressure:</b>	Factory set at 1500 PSI for first 50 hours of diesel break-in. After break-in, set to 1900 PSI.
<b>Hydraulic Flow:</b>	6 to 18 GPM
<b>Operating Temp:</b>	110°F / 43.3°C - 175°F / 79.4°C
<b>Electrical:</b>	Nema 4 Electrical Controls 12 VDC
<b>Pendant:</b>	Pendant cable of 12 ft plus 50 ft. extension
<b>Lifting System:</b>	5 point lifting system
<b>Filter:</b>	Spin-on Filter
<b>Heat Exchanger:</b>	Air Over Oil
<b>Gear Pump:</b>	Standard Gear Pump
<b>Dimensions:</b>	54" H x 26.5" W x 45.5" L
<b>Weight:</b>	935 lbs dry weight (no battery)



12.02.2020